

PLATFORM SCALE type SA 235



WATERPROOF IP 67



- ▶ Capacities: 1,5 - 3 - 7,5 - 15 kg
- ▶ Reading accuracy up from 0,1 gram
- ▶ For internal applications
- ▶ Platform size 22 x 18 cm
- ▶ Stainless steel exterior
- ▶ Waterproof to IP 67 (submerged at 1 m)
- ▶ Built in battery and charger

SATEX

SATEX

- ▶ High resolution selectable
- ▶ Stainless steel exterior
- ▶ IP 67 water and dust protected
- ▶ Piece counting program
- ▶ 2 selectable weight margins
- ▶ Built in battery and charger



Well ordered operation and reading

Stainless steel weighplatform

Stainless steel housing

Operation keys with tactile feedback

High speed LED display

DISPLAY

Large, clearly readable LED figures, 15 mm high. Display speed 10 Hz with adjustable filters.

The reading may be tared (set zero) over 100% of the weighing range. Automatic zero adjustment keeps the the readang at an exact at no load.

ACCURACY

Choose out of 3 settings of the multi interval *) reading accuracy:

- H1 = standard readingreading
- H2 = reading 2 x more accurate
- H3 = reading 5 x more accurate

*) 2 weighing ranges: the first one is 2 x more accurate as the second

Adjustable in the User Mode menu.

OPERATING KEYS

Real switches, no membrane buttons:

- set zero (near gross zero)
- set tare (set zero over total weighing range)
- piece counting and check weighing
- change-over: weighing - checkweighing/ piececounting

WATERPROOF IP 67

The exterior of the housing is from stainless steel with rounded corners. The electronic parts are mounted in a second internal enclosure, that is completely waterproof sealed to IP 68. According to the norm IP 67 the scale may be submerged in clean water for 1 hour at 1 m depth without incoming water will cause malfunton of the scale.

MENU FUNCTIONS

- Adjustable reading accuracy
- 2 settable weightmargins for checkweighing
- Auto zero : off - settable
- Display speed : adjustable
- Auto off scale : off - adjustable time delay
- Adjustment with 1 or 3 point calibration

EXCITATION

Built in battery and charger for max. 170 hours continuous operation.

Supply with 230 V mains cable and store room in the bottom of the scale.

After a selectable time of no use, the scale switches off automatically, in order to save the battery.

This auto off function may be switched off.

MODELS		TECHNICAL INFORMATIONS				
Order number	Platform size	Weighing capacity	display reading accuracy per:			
			2 ranges	multi interval type:		
				H1	H2	H5
SA 235 - 1	22 x 18 cm	0 - 1.5 kg	0 .. 0,75 kg 0,75 .. 1,5 kg	0,5 g 1 g	0,2 g 0,5 g	0,1 g 0,2 g
SA 235 - 3		0 - 3 kg	0 .. 1,5 kg 1,5 .. 3 kg	1 g 2 g	0,5 g 1 g	0,2 g 0,5 g
SA 235 - 7		0 - 7,5 kg	0 .. 3 kg 3 .. 7,5 kg	2 g 5 g	1 g 2 g	0,5 g 1 g
SA 235 - 15		0 - 15 kg	0 .. 7,5 kg 7,5 .. 15 kg	5 g 10 g	2 g 5 g	1 g 2 g
Accuracy	Better as + or - 1 scale division, H5 better as + or - 2 scale divisions					
Calibration	1 or 3 points adjustment via the menu, using accurate weights					
Dimensions	23,5 x 28,5 x 11 cm (wxdxh) own weight 3.6 kg					
Construction	Stainless steel housing and platform, internal housing IP 68 sealed plastic, 4 leveling feet and level indicator, loadcell with overload protection, inside storage of mains cable					
Reading	LED display with 15 mm high figures, 3 signal Led's for checkweighing					
Filter	Adjustable speed and filtering for application in unstable environment, auto zero time adjustable and may be switched off					
Auto off	Automatic switch off of the scale, if not used, adjustable: off, 5, 10, 20, 60 minutes					
Excitation	Built in rechargeable battery and charger, stand alone operation for 170 hour continuously. Charging time 16 hours.					
Metrology	for internal use only					
Packing	Carton box, 34 x 28 x 16 cm, (wxdxh), gross weight 3.9 kg					